

ERGOWOOD® Precision Modular Ergonomic Flooring



Other patents pending

ERGOWOOD® is a highly-technical precision ergonomic solution for dynamic work environments. This innovative product offers superior ergonomic comfort, safety, and protection for your workforce. ERGOWOOD® is visually appealing and greatly reduces trips, falls, sprains and strains compared to anti-fatigue matting in high-movement jobs.

PERFORMANCE ADVANTAGES

- ✓ Absorbs impact stress, relieves fatigue, and reduces discomfort from concrete and steel floors
- ✓ Flexible, seamless surface connection for safe and stable footing
- ✓ Boosts morale while helping protect and preserve musculoskeletal health
- ✓ Advanced compression resistance (zero set formulation) prevents permanent deformation under sustained load
- ✓ Ideal surface for active movement and long-duration standing
- ✓ Fully cohesive integration in general assembly or production lines, paint operations, body shops, and material handling environments.
- ✓ Quick and easy installation



Optimum Performance and Comfort



Sure-footed Traction Prevents Slipping



Reduces Trips and Falls



Housekeeping Friendly



Flame Retardant



100% Recyclable




Assembled in the USA

PRECISION CUTS FOR ANY SHAPE OR SIZE

CNC Router



T-Connector
Simple installation!



L-Molding
90° edge in lieu of yellow border



Cross Section

OMNISPORTS

(ergonomic surface, confirmed by ASTM laboratory tests)



Custom sizes available to fit your exact workspace. Contact us for a fast, tailored quote. Email sales@ergobuddy.com or call 1-800-229-1930.

TRUSTED BY LEADING COMPANIES WORLDWIDE.

ERGOBUDDY.COM

ERGOWOOD® Precision Modular Ergonomic Flooring



ASTM TEST DATA

OMNISPORTS

- 25-year warranty
- Meets ASTM 970 205psi (Static Load Tolerance)
- Achieves Class 2 Force Reduction requirements of ASTM F2772-11
- Compression force deflection 27.6 psi: ASTM D3574-11
- Compression set 0.5 at 24 hours: ASTM D1056-07
- Shock absorption (force reduction): ASTM F2569 and F2772
- Floor Slip Rating: Minimum of R12
- Surface finish effect-coefficient of friction: Min. 0.5
- ASTM E303
- Reaction to fire ASTM 648 (class, radiant panel)
- Microbial resistance ASTM G21 (backing) no growth

ECOGRIP

- 10-year warranty
- Compression force deflection 90 psi ASTM D3574-11
- Compression set 10 at 24 hours ASTM 1056-07
- Coefficient of friction Dry 1.31 common wet 1.07 ASTM 1894-08
- Fire test NFPA type 1 rated
- Bacteria and mildew resistance: excellent ASTM 6-21
- Chemical resistance per ASTM 0.543.
- Additional tests available upon request.

OMNISPORTS



ECO-GRIP®



OMNISPORTS and ECO-GRIP® share the same dimensions and can be seamlessly integrated together within the same workspace to meet changing environmental or operational needs.

OMNISPORTS

ECO-GRIP®